



ASSURED ENERGY
Product Liability Insurance QBE



30 YEAR LINEAR POWER WARRANTY
ANNI GARANZIA LINEARE PRODUZIONE

20 YEAR PRODUCT WARRANTY
ANNI GARANZIA PRODOTTO



12V DC MODULES
FOR OFF-GRID SOLUTIONS



SUITABLE FOR: **SOLAR KITS,**
RVS, BOATS AND CABINS



MAXIMUM ADAPTABILITY

CELLS



TYPE:
POLY 3BB-4BB

FRAME



BACKSHEET



ELECTRICAL CHARACTERISTICS (STC)*

| | OS10P | OS20P | OS30P | OS50P |
|-----------------------------|---------------------------------|-----------------------------|---------------------------------|---------------------------------|
| Nominal Output (Pmax) | 10 W | 20 W | 30 W | 50 W |
| Voltage at Pmax (Vmp) | 16.5 V | 18.6 V | 17.65 V | 17.72 V |
| Current at Pmax (Imp) | 0.61 A | 1.08 A | 1.70 A | 2.83 A |
| Open Circuit Voltage (Voc) | 20 V | 22.14 V | 21.17 V | 21.26 V |
| Short Circuit Current (Isc) | 0.67 A | 1.16 A | 1.90 A | 3.17 A |
| Module Efficiency | 9.84% | 10.84% | 10.59% | 13.61% |
| Solar Cells | 36 (4x9) | 36 (4x9) | 36 (2x18) | 36 (4x9) |
| Cells Dimensions | 52x36mm / 2x1.4" | 78x52 mm / 3x2" | 156x39 mm / 6x1.5" | 156x52 mm / 6x2" |
| Cable | - | - | 50 cm + MC4 | 50 cm + MC4 |
| Dimensions | 415x245x17 mm 16.3x9.6x0.67" | 535x345x25 mm 21x13.5x1" | 798x355x30 mm 31.4x13.9x1.2" | 545x674x30 mm 21.5x26.5x1.2" |
| Weight | 1.3 Kg / 2.86 lbs | 2.2 Kg / 4.85 lbs | 3.4 Kg / 7.49 lbs | 4.2 Kg / 9.26 lbs |

ELECTRICAL CHARACTERISTICS (STC)*

| | OS80P | OS100P | OS150P |
|-----------------------------|---------------------------------|----------------------------------|----------------------------------|
| Nominal Output (Pmax) | 80 W | 100 W | 150 W |
| Voltage at Pmax (Vmp) | 17.78 V | 17.80 V | 17.64 V |
| Current at Pmax (Imp) | 4.50 A | 5.62 A | 8.51 A |
| Open Circuit Voltage (Voc) | 21.33 V | 21.36 V | 21.17 V |
| Short Circuit Current (Isc) | 5.03 A | 6.26 A | 9.51 A |
| Module Efficiency | 12.76% | 14.40% | 15.04% |
| Solar Cells | 36 (4x9) | 36 (4x9) | 36 (4x9) |
| Cells Dimensions | 156x93 mm / 6x3.6" | 156x104 mm / 6x4" | 156x156 mm / 6x6" |
| Cable | 50 cm + MC4 | 50 cm + MC4 | 50 cm + MC4 |
| Dimensions | 930x674x35 mm 36.6x26.5x1.4" | 1030x674x35 mm 40.5x26.5x1.4" | 1480x674x35 mm 58.3x26.5x1.4" |
| Weight | 7.15 Kg / 15.76 lbs | 8 Kg / 17.64 lbs | 9.9 Kg / 21.82 lbs |

*STC: (Standard Test Condition) Irradiance 1000W/m²; Module Temperature 25°C; Air Mass 1.5

It is important to point out, that all technical specifications, information and figures contained in this datasheet are estimated values. Peimar reserves the right to change the technical specifications, information and figures contained in this document at any time without notice

US_06/2019