


SLP050-12U

High Efficiency Multicrystalline PV Module

Electrical Characteristics	SLP050-12U
Product code	055011209
Maximum power (Pmax)	50W
Voltage at Pmax (Vmp)	18.64V
Current at Pmax (Imp)	2.68A
Open-circuit voltage (Voc)	22.18V
Short-circuit current (Isc)	2.85A
Temperature coefficient of Voc	-(80±10)mV/°C
Temperature coefficient of Isc	(0.065±0.015)%/°C
Temperature coefficient of power	-(0.5±0.05)%/°C
NOCT (Air 20°C; Sun 0.8kW/m² wind 1m/s)	47±2°C
Operating temperature	-40°C to 85°C
Maximum system voltage	1000V DC
Power tolerance	± 5%



*STC: Irradiance 1000W/m², AM1.5 spectrum, module temperature 25°C

*NOCT:Nominal operating cell temperature (the data is only for reference)




Module Diagram

Dimensions in brackets are in inches.
Un-bracketed dimensions are in millimeters.
Unit: mm[in.]



Junction Box
Top View(Lid Open)




Section A-A

Features

- Nominal 12V DC for standard output.
- Outstanding low-light performance.
- Heavy-duty anodized frames.
- High transparent low-iron,tempered glass.
- Rugged design to withstand high wind pressure, hail and snow load.
- Aesthetic appearance.

Characteristics



SLP050-12U I-V Curves

Specifications	SLP050-12U
Cells	Polycrystalline silicon solar cell
No. of cells and connections	36(4X9)
Module dimension	534mm[21.02in.]x675mm[26.57in.]x30mm[1.18in.]
Weight	4.65kg[10.25lbs]
Packing information(Carton)	720mm[28.35in.]x580mm[22.83in.]x95mm[3.74in.]/(2pcs/ctn)

*Limited warranty: 5-year limited warranty of materials and workmanship; 10-year limited warranty of 90% power output; 25-year limited warranty of 80% power output. For detail, please contact us.

*Specifications are subject to change without notice at any time.