

MONO


POLY



HELIENE

72^P

72-CELL POLYCRYSTALLINE MODULE



340 Wp

MAX POWER OUTPUT

17.5%

MAX EFFICIENCY

10 YEAR

PRODUCT WARRANTY

25 YEAR

LINEAR PERFORMANCE GUARANTEE



H-BLACK INTEGRATION AVAILABLE (ALL-BLACK MODULE)



AVAILABLE IN 1000V OR 1500V SYSTEM VOLTAGE RATING



MANUFACTURED ACCORDING TO INTERNATIONAL QUALITY SYSTEM STANDARDS: ISO9001



GUARANTEED POSITIVE POWER SORTING: [-0 : +4.99 WP]


HELIENE INC. IS A PREMIER SOLAR MODULE MANUFACTURER, SERVICING THE GROWING SOLAR ENERGY MARKETS OF NORTH AMERICA.

COMBINING PROVEN EUROPEAN TECHNOLOGY WITH NORTH AMERICAN INGENUITY ALLOWS HELIENE TO MAKE A REAL COMMITMENT IN PROVIDING SMARTER ENERGY CHOICES FOR THE FUTURE.


HELIENE
www.heliene.com

LINEAR PERFORMANCE GUARANTEE



10 YEAR WORKMANSHIP WARRANTY • 25 YEAR LINEAR PERFORMANCE GUARANTEE



DIMENSIONS FOR HELIENE 72P SERIES MODULES



I-V CURVE FOR HELIENE 72P SERIES



CERTIFICATIONS



ELECTRICAL DATA (STC)

Peak Rated Power	P_{mpp} (W)	340	335	330	325	320	310
Maximum Power Voltage	V_{mpp} (V)	38.45	38.05	37.54	37.42	37.40	37.20
Maximum Power Current	I_{mpp} (A)	8.92	8.90	8.85	8.745	8.64	8.40
Open Circuit Voltage	V_{oc} (V)	46.37	46.28	46.26	46.11	45.96	45.66
Short Circuit Current	I_{sc} (A)	9.45	9.20	9.13	9.05	8.97	8.81
Module Efficiency *	Eff (%)	17.5	17.3	17.0	16.7	16.5	16.0
Maximum Series Fuse Rating	MF (A)	15	15	15	15	15	15
Power Output Tolerance		[- 0, + 4.99] Wp					

STC - Standard Test Conditions: Irradiation 1000 W/m² - Air mass AM 1.5 - Cell temperature 25 °C

* Calculated using maximum power based on full positive output tolerance [-0, +4.99] Wp

MECHANICAL DATA

Dimensions (L x W x D)	1956 x 992 x 40 mm (77 x 39 x 1.6 inch)
Weight	21.9 kg (48.28 lbs)
Output Cables	1.2 m (47.2 inch) symmetrical cables with MC4 type connectors
Junction Box	IP-67 rated with bypass diodes
Frame	Double webbed 15 micron anodized aluminum alloy
Front Glass	Low-iron content, high-transmission PV solar glass
Solar Cells	72 Polycrystalline cells (156 x 156 mm)

CERTIFICATIONS

UL Certification	ULC/ORD-C1703-1, UL1703
IEC Certification	Optional

All Heliene modules are certified under the California Energy Commission (CEC) Listing Report

TEMPERATURE RATINGS

Nominal Operating Cell Temperature (NOCT)	+45°C (±2°C)
Temperature Coefficient of P_{max}	-0.43%/°C
Temperature Coefficient of V_{oc}	-0.32%/°C
Temperature Coefficient of I_{sc}	0.05%/°C

PACKAGING CONFIGURATION

Modules per box:	26 pieces
Modules per 53' trailer:	780 pieces

MAXIMUM RATINGS

Operational Temperature	-40°C - +85°C
Max System Voltage	1000V (*1500V) *Optional

WARRANTY

10 Year Manufacturer's Workmanship Warranty

25 Year Linear Power Guarantee

(Refer to product warranty page for details)

CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT. Specifications included in this datasheet are subject to change without notice.